

Hydraulic Pad Jack Cylinders

Pad jacks are shortest form of hydraulic cylinder available their extremely low profile means they can fit into the smallest of gaps. Pad jacks can also be used as extensions by increasing the stroke by stacking on other cylinders.

Capacity Range: 1 tonne to 150 tonne
Max Pressure 10`000PSI (700 BAR)
Stroke Range: 6mm to 17mm
Single Acting Spring Assisted Return
Piston Hard Chromed
Inside Re-Polished
Outside Blasted & Chromed



www.liftsafesolutions.co.uk

ORDER CODE	CAPACITY (ton)	STROKE (mm)	AREA OF FORCE (cm ²)	OIL CAP (c.c)	A (mm)	B (mm)	C Ø (mm)	D Length x Width (mm)	E Ø (mm)	H Ø (mm)
SLS50	5	6	6.5	4.5	33	39	28.5	58 X 41	31	25.4
SLS100	10	12	14.5	18	42	54	36	82 X 55	44	38
SLS200	20	12	28.7	34	51	63	49.3	101 X 76	60	50.8
SLS300	30	13	42.1	54	58	71	52.3	117 X 95	73	63.5
SLS500	45	16	62.1	102	66	82	66.5	140 X 114	90	70
SLS750	75	16	102.6	166	79	95	76.2	165 X 140	115	82.5
SLS1000	90	16	126.7	212	85	101	76.2	178 X 152.5	130	92
SLS1500	150	17	198.1	342	100	116	117	216 X 190	160	115

ORDER	G Ø (mm)	K (mm)	J Ø (mm)	H1 (mm)	L (mm)	M (mm)	WEIGHT (kgs)
SLS50	5.5	16	9.5	1	20	22	1.0
SLS100	7.5	19	11	1	28.5	34	1.4
SLS200	10	19	15	1	39	39	3.1
SLS300	10	19	16	2	47	44	4.5
SLS500	11	19	19	2	55	55	6.8
SLS750	13.5	19	20.5	2	69	66	11.3
SLS1000	13.5	19	20.5	2	76	74	14.5
SLS1500	13.5	23	23	2	95	82	26.3

